



ZENITH EP-1

EXTREME PRESSURE GREASE

ZENITH EP 1는 엄선된 극압 첨가제를 사용, 내하중 성능이 매우 우수하여 고하중에도 효과적으로 윤활막을 유지하여 극압성이 요구되는 자동차 및 산업용 장비에서 최적의 성능을 발휘 합니다.

APPLICATIONS

- 고부하 및 충격하중으로 극압성이 요구되는 장비 및 산업용 장비의 다목적 그리스로 우수한 성능을 발휘합니다.
- 고부하 혹은 충격하중으로 극압성이 요구되는 윤활개소에 적합 합니다.
- 우수한 수세내수성 및 점착성으로 부식을 방지합니다.
- 산화안정성 및 기계적 안정성이 우수하며 낮은 유분리성으로 장기간 사용이 가능합니다.
- 사용온도 범위: -20 ~ 140 °C

PHYSICAL-CHEMICAL CHARACTERISTICS

색 상 (Color)	Yellow brown
NLGI 등급	1
기 유 (Base Oil)	Mineral Oil
주도 Penetration(mm)	320
적 점 Dropping Point°C	230
이유도 Oil Separation (%)	3.2
산화안정도 Bomb Oxidation Kg/cm ² DROP (98.9°C X 100hrs)	0.3
동판부식 100°C 24Hr	1a (변화 없음)

The typical properties shown on this product data sheet should not be used as a basis for preparing specifications. Refer to our product Material Safety for detailed safety information.

The data given herein are average values and can be modified in further product developments. The end user must check the suitability of the product for each particular application. Unless our technical department is aware and agree on the specific service conditions and application we cannot provide manufacturer liability or property guarantee.